FLIGHT LIGHT

LED Taxiway Edge Light FAA L-861T

Compliance and Applications

Certified to FAA AC 150/5345-46 (Current Edition) FAA Engineering Brief No. 67

Our ETL Certified L-861T LED Taxiway Edge Lights are used to mark the outlines of taxiways at general aviation and medium-sized airports. Each L-861 is constructed from a die cast aluminum body, powder coated in aviation yellow. The L-861s feature long-life LEDs that reduce power consumption, increase reliability and reduce operating costs. A rugged cord is included with a rubberized L-823 style connector to connect to the secondary of a 6.6A isolation transformer. Each L-861 includes a 1.5" (standard) or 2.0" frangible coupling to attach the fixture to a L-867 style base plate or mounting stake. Standard mounting heights are 14, 24 and 30 inches.

Features

- Applicable for L-861T (L) requirements.
- Colored glass lens for easy daytime recognition.
- Double sealing system creates watertight head assembly.
- Rugged solid state components.
- Complies with intensity requirements on 3 or 5 step regulators.
- Durable powder coat finish lasts longer.
- Reduces power consumption.
- Long-life LEDs.
- Cord set sealed to prevent insect entry.
- Threaded 1.5" frangible coupling or optional 2" thread matches existing baseplates/stakes.



Ordering Codes

Fixture	Lens Colors	Mounting Height*	Fixture Options
75-861L	B: Blue	14 : 14" (standard)	1: 1.5" Frangible Coupling (FL-FC1.5)
		20 : 20" (extended)	2: 2" Frangible Coupling (FL-FC2.0)
		24 : 24" (extended)	5: Optional heater
		30 : 30" (extended)	V: 90-260 VAC (not ETL certified)

^{*} Other heights available.

VA Loads

WITHOUT HEATER					
Color	VA Load*	Transformer Size			
Blue	11.22	10/15W			

WITH HEATER					
Color	VA Load*	Transformer Size			
Blue	24.42	20/25W			

^{*} VA loads are applicable for certified lights.

+1.916.394.2809 Fax

^{+1.916.394.2800} Worldwide