

Series Isolation Transformers

FAA L-830 / L-831

Compliance and Applications

FAA L-830, AC 150/5345-47

Series isolation transformers are used to isolate high operating voltages for constant current lamps in series circuits.

Features

- Our transformers are made of flat laminations in an ETI formation for 6.6A and 20A applications.
- Encapsulated in synthetic rubber for durability and dielectric strength. Waterproof assembly suitable for above ground installation or direct burial.
- Two Primary Leads: terminated with molded L-823 Style 2 (male) and Style 9 (female) connectors. Standard length 24", 8/1 cable. Rated to 25A and 5,000V.
- One Secondary Lead: terminated with a molded L-823 Style 8 (female) connector, "ball-type". Optional Style 7 (female) connector, "straight design" for use with signs and extension cords. Standard length 48", 12/2 600V cable. Rated to 20A and 600V.



- Optional ground (earthing) lead (1). 36" long #12 AWG 600V ground lead, terminated in a ring terminal. To order add the letter "G" to the model number.
- All transformers undergo 100% quality testing before they are shipped: visual inspection, HIPOT after heating and 12 hour soaking (15,000V primary, 5,000V secondary), and ratio testing.

Product Specifications

FAA 60 Hz Part #	FAA 50 Hz* Part #	Watts	Prim. Amps	Sec. Amps	Weight (lb.)	Volume (cu. ft.)
TR-L830-1	TR-L831-1	30/45W	6.6	6.6	6.5	.2
TR-L830-2	TR-L831-2	30/45W	20	6.6	6.5	.2
TR-L830-3	TR-L831-3	65W	6.6	6.6	7	.2
TR-L830-4	TR-L831-4	100W	6.6	6.6	10	.4
TR-L830-5	TR-L831-5	100W	20	6.6	10	.4
TR-L830-6	TR-L831-6	200W	6.6	6.6	11	.4
TR-L830-7	TR-L831-7	200W	20	6.6	11	.4
TR-L830-8	TR-L831-8	300W	6.6	20	22	.6
TR-L830-9	TR-L831-9	300W	20	20	22	.6
TR-L830-10	TR-L831-10	300W	6.6	6.6	22	.6
TR-L830-11	TR-L831-11	300W	20	6.6	22	.6
TR-L830-12	TR-L831-12	500W	6.6	20	24	.7
TR-L830-13	TR-L831-13	500W	20	20	24	.7
TR-L830-14	TR-L831-14	500W	6.6	6.6	24	.7
TR-L830-16	TR-L831-16	10/15W	6.6	6.6		
TR-L830-17	TR-L831-17	20/25W	6.6	6.6		
TR-L830-18	TR-L831-18	150W	6.6	6.6	11	.4

* To order ground (earthing) lead add the letter "G" to the model number.

+1.800.806.3548 USA
+1.916.394.2800 Worldwide

www.flightlight.com
sales@flightlight.com

Flight Light Inc., 2708 47th Ave.
Sacramento, CA, 95822, USA