L-810 LED Steady-Burning Red Obstruction Light

Compliance and Applications

- Not FAA Approved under AC 150/5345-43J
- IP67 Certified

Compliant to:

- ICAO Annex 14, Low Intensity Obstacle Light, Type B
- DGAC of Mexico
- MIL-C-7989

Our L810LED omni-directional, red, steady-burning obstruction light is designed for marking tall structures such as buildings, towers, masts, cranes, meteorological towers, chimneys and other hazards to aircraft. This energy-saving LED light is a direct replacement for incandescent fixtures, providing years of reliable and maintenance-free operation. Available in single, double, and retrofit configurations; optional solar drive package.

Why Our L810LED is Better

- Direct replacement for existing incandescent light
- Lasts up to 10 times longer than an incandescent light
- Uses 96% less power than an incandescent light
- No regular maintenance
- Available in single and dual configurations with bottom or side conduit outlets
- Can be operated in steady-burning or flashing mode (controller not supplied)
- Photocell option for automatic activation at night
- Self-contained wiring compartment eliminates additional boxes
- Weather/corrosion resistant
- IP67 Ingress Protection rating for dust and water
- Lens made from durable, UV-stabilized LEXAN polycarbonate
- Resistant to shock and vibration
- Operates from -67°F to +131°F (-55°C to +55°C)
- 5 year warranty

Specifications

- Construction: Machined aluminum, stainless steel hardware
- Finish: Red powder coat
- Power Consumption: 2.4W (DC); 4.2W (AC) [100CD: 4.5W (DC); 9.6W (AC)]
- Power Source: 100-277 VAC, 12-48 VDC
- Intensity: 32.5 candelas ("100 candelas" option available)
- Light Output Wavelength: Red 615 nm
- Dimensions: 5.65" dia. x 7.75" height (single)
- Weight: 3.2 lb. (single); 7 lb. (double)
- LED Estimated Lifetime: 70,000+ hours
- IP Rating: IP67
- Wind Loading: Effective Projected Area of the L-810 with single mounting base is 23.125 square-inches



Optional Low Surface Mount



Optional 2" Pole Mount



Shown with Frangible Coupling and Floor Flange




Single L-810 LED Steady-Burning Red Obstruction Light



Marine Treated Option:

- *Recommended for harsh, high-salt coastal and marine environments.*
- *Protects fixture finish from salt damage and prevents corrosion.*
- *3-Step Powder Coat: 1) Primer, 2) Epoxy powder base coat and glossy polyester gray (RAL 7030) powder finish coat, 3) Oven curing.*



Double L-810 LED Obstruction Light with Optional Photocell

+1.800.806.3548 USA
+1.916.394.2800 Worldwide

www.flightlight.com
sales@flightlight.com

Flight Light Inc., 2708 47th Ave.
Sacramento, CA, 95822, USA


Product specifications may be subject to change without prior notice. Verify current specifications when ordering. © Flight Light Inc. | 10/29/2026

Spare Parts

Part Number	Description
FL-810LED-AC	100-277 VAC LED Replacement Light Head
FL-810LED-DC	12-48 VDC LED Replacement Light Head



Alarm Line Option:
For AC and DC model fixtures, the blue wire (18AWG) is defined as the Alarm Line. When the red LED fails, the fixture's input voltage for the fixture will be present at this wire. For AC and DC model fixtures, during normal operation (LED ON), it will have 0 VAC and 0 VDC respectively at the blue wire; in case of LED failure (turning off), it will energize the blue wire to the fixture's input voltage, 100-277 VAC for AC models and 12-48 VDC for DC model fixtures.



Wire Color Guide

100-277 VAC	12-48 VDC
L: Black	+: Red
N: White	–: Black
GRD: Green	GRD: Green
Alarm Line: Blue	Alarm Line: Blue

Shipping Information:
Single: 3.2 lb. (1.45 kg); 10" x 10" x 10" Carton

Double: 7 lb. (3.17 kg); 15" x 15" x 10" Carton

L-810 LED Ordering Codes

Fixture	Color	Power	Fixture Style	Mounting[1]	Options
FL-810L	**R:** Red	**AC:** 100-277 VAC **DC:** 12-48 VDC	**S:** Single **D:** Double	**34B:** 3/4" Hub - Bottom **10B:** 1" Hub - Bottom **34S:** 3/4" Hub - Side **10S:** 1" Hub - Side **FF:** Floor Flange **LSM:** Low Surface Mount **PM:** 2" Pole Mount[2]	**100C:** 100 Candelas **AL:** Alarm Line[3] **H:** High Temperature[4] **P:** Photocell **T1:** 120VAC Transfer Relay **T2:** 240VAC Transfer Relay **MT:** Marine Treated

[1] 1-1/2" Frangible Coupling (FL-FC1.5) UNF threads are not compatible with NPT threaded junction boxes. [2] 2-3/8" O.D. tenon adjustable for 2.25"-2.75" poles. [3] **CAUTION! For AC model fixtures, the Alarm Line (blue wire) will be energized to a high AC voltage (fixture's input voltage 120-277VAC) during a failure of the LED.** [4] For locations with high temperatures above +131°F (+55°C).



Night Vision Compatible version available. See flightlight.com for details.

Obstruction Lighting Controls

Lighting controls are designed for use when multiple obstruction light fixtures are to be controlled with common electronics. The electronic control module comes in a cast iron device box with threaded hubs on both top and bottom. Replacement modules (controls without device box) are also available upon request.

Photocells

- **Model 81020:** 105-305VAC, 1000W photocell. FAA style photocells activate at 35 ft-cd and turn off at 52 ft-cd. Instant ON photocell has 3-5 second time delay that prevents activation and de-activation from momentary light conditions. Does not come with device box, includes 1/2" threaded male fitting.
- **Model 81021** [CALL FOR AVAILABILITY]**:** 120/240VAC, 4800W photocell. Meets FAA/FCC requirements for obstruction lighting. Energized at 35 ft-cd and de-energized at 60 ft-cd. Time delay eliminates contact chatter. Contains dual 20A load contacts. Front plastic housing mounts to cast aluminum junction box (included).
- **Model 81022:** Hazardous Location Photocontrol Unit. Outdoor lighting control for exterior lighting in hazardous locations: explosion proof, dust-ignition proof, and weatherproof. Nominal Voltage 50/60 Hz: 120/208/240/277VAC. Voltage Range: 105-305. Housing: sand cast copper-free aluminum - epoxy powder coated.



Model 81020



Model 81021

Photocell Ordering Codes

Part Number	Description
FL-81020	Photocell only (105-305VAC, 1000W max)
FL-81021 [CALL FOR AVAILABILITY]	Photocell with aluminum box (120VAC, 4800W max)
FL-81021-2 [CALL FOR AVAILABILITY]	Photocell with aluminum box (240VAC, 4800W max)
FL-81022	Hazardous Location Photocontrol Unit (120/208/240/277VAC)



Model 81022

+1.800.806.3548 USA
+1.916.394.2800 Worldwide

www.flightlight.com
sales@flightlight.com

Flight Light Inc., 2708 47th Ave.
Sacramento, CA, 95822, USA

Product specifications may be subject to change without prior notice. Verify current specifications when ordering. © Flight Light Inc. | 10/29/2026