



Flight Light Inc.  
 2708 47th Ave.  
 Sacramento, California, U.S.A.  
 95822-3806

PH (916) 394-2800    FX (916) 394-2809  
 TF (800) 806-3548    EM info@flightlight.com

**Elevated LED  
 Runway Guard Light (RGL)  
 Certified FAA L-804**

### Compliance and Applications

Certified to FAA AC 150/5345-46 (Current Edition) for L-804 applications; EB-67.

Our LED Runway Guard Light (RGL) provides a warning to pilots or drivers of ground vehicles that they are approaching an active runway. The RGL increases hold position visibility, especially during bad weather.

### Features

- Uses two 21W LED optical assemblies.
- Average LED life of 50,000 hours.
- Energy efficient LED lighting reduces circuit load.
- Operates on FAA constant current regulators, either 3 or 5 step. 120V systems also available.
- Adjustable light beam elevation with positive locking in one-degree increments.
- Minimum average intensity exceeds 3000 candelas.
- Alternately flashes 45-50 times per minute.
- Easy to maintain - no special tools required.
- High strength, powder coated frame and aluminum housing with stainless steel hardware.
- Independent black signal head visors provide protection during inclement weather conditions and enhanced contrast during daylight operations.
- 2-inch frangible column and tether with positive lock canting.
- Supplied with tether and anti-rotation locking plate.
- 300 MPH jet blast resistant.
- Base unit supplied with a dry contact output for monitoring.
- Monitoring is available.



### Ordering Codes

Fixture	Power	Monitoring	Height
<b>75-RGL</b>	<b>01C:</b> Current (Mode 1 Series Powered) <b>02V:</b> Voltage (Mode 2 Parallel Powered) <b>DC:</b> Low Voltage (24VDC)	<b>U:</b> Unmonitored <b>M:</b> Monitored	<b>S:</b> 14" standard height* <b>T:</b> 26" height for applications in snow

\* Standard height is from the ground up to the bottom of the light emitting surface. Custom heights may be specified.

**Visit our web site: [www.flightlight.com](http://www.flightlight.com)**